

User Manual – Cooling Solax X3 Hybrid G4 – SXX3G401-T

Dear customers,

thank you for your trust and for purchasing this product. This user manual is part of the product. It contains important instructions for commissioning and operation. If you hand the product over to another person, make sure to also provide this manual. Keep this manual for future reference!

Product Description

Additional active cooling for Solax X3 Hybrid G4 inverters, designed to reduce the inverter temperature under load by 15–30 °C (depending on installation conditions). Helps prevent power derating during hot days and prolongs the service life of electronic components.

Package Contents

- Power supply SAW30-240-1200G, 230V AC / 24V DC
 - Cooling rail with thermostat and NTC sensor
-

Specifications

Compatibility:

Solax X3 Hybrid G4: 5.0-D/M, 6.0-D/M, 8.0-D/M, 10.0-D/M, 12.0-D/M, 15.0-D/M

DRAŽICE IN.HYBRID COMPACT: 5.0K-D/M, 6.0K-D/M, 8.0K-D/M, 10.0K-D/M, 12.0K-D/M, 15.0K-D/M

Power supply: 24V DC (5.5*2.1), min. 0.8A source

Active cooling: 3 × Sunon 60 mm fans, Vapo (MagLev), rated lifetime 70,000 h, airflow total 138 m³/h

Consumption: Stand-by 0.5 W, operation 7 W

Safety Instructions

- The device is intended for indoor use only.
 - Do not use in humid, dusty, flammable, or explosive environments.
 - Do not open, repair, modify, or tamper with the device – doing so voids the warranty.
 - If the cooling is not connected to power and regulation does not function, the cooling must be promptly removed from the inverter. Regularly check cooling functionality.
 - Always follow the rules, instructions, and warnings provided by the inverter manufacturer during installation, removal, and handling.
 - If not properly mounted or connected, cooling may not reduce inverter temperature effectively and can even increase it – check operation after installation.
 - If disconnected from the power supply, cooling must be promptly removed from the inverter.
 - Use only a 24 V DC, min. 0.8 A power supply.
 - Do not use the device if the power cable, casing, or fans show visible damage.
 - Prevent foreign objects from entering the fans during operation.
 - Never cover the device – ensure free airflow.
 - Not intended for use by children or persons with reduced capabilities without supervision.
 - Do not install or use near water sources (sinks, pools, showers, etc.).
 - Always disconnect from power before cleaning and wait until fans have completely stopped.
-

Installation Instructions

Install by sliding the unit under the inverter and then attaching it to the lower ends of the fins (snap-in).

Route the sensor behind the inverter and place it on the fins in the left third of the middle section. Insert the sensor from the rear and push forward until it holds firmly. Do not place the sensor in the middle of the fins, as airflow would affect temperature measurement.

Removal is done by tightening the side locking screws fully and sliding the cooling unit out. Do not tighten the locking screws before installation.

Both the inverter and cooling must be powered off before installation or removal.

Function Description

After connecting the power supply and switching on via the side switch, the thermostat displays the temperature at the sensor location. If the temperature exceeds the set threshold (P0), cooling turns on. When the temperature drops below the lower set threshold (P1), cooling turns off. Cooling draws air from below.

Adjusting Cooling On/Off Temperature

- SET – enter menu/confirm selection
- Up/Down buttons – increase/decrease temperature, switch between P0, P1, P2, P3
- The set values are stored in the internal memory of the thermostat and remain saved even after disconnecting power.

P0 – Temperature at which the thermostat (cooling) switches on. Default: 40 °C. Use SET, select P0 with arrows, adjust value, confirm with SET.

P1 – Temperature at which the thermostat (cooling) switches off. Default: 35 °C. Use SET, select P1 with arrows, adjust value, confirm with SET.

P2 – Temperature measurement correction (offset). If the thermostat shows e.g. 1 °C higher than the actual value, set correction to –1 °C. Range: ±10 °C. Confirm with SET.

P3 – Delay time for thermostat switching. Set with arrows, confirm with SET. Range: 0–10 minutes (recommended not to use).

OUT indicator: When lit, the thermostat (cooling) is active.

Storage and Cleaning

- Operating environment: temperature 5 °C–55 °C, relative humidity <70%
 - Storage conditions: temperature 0 °C–55 °C, relative humidity <70%
- The product requires no maintenance. Clean the casing with a soft cloth slightly dampened with water only. Do not use abrasive agents or solvents (paint or varnish thinners), as these may damage the product. Clean once per year. Cleaning may only be carried out when the cooling is removed and disconnected from the power supply.
-

Disposal Information

For environmental protection, the device must not be disposed of with household waste at the end of its service life. Dispose of it in accordance with local regulations at designated collection points. Dispose of in compliance with Directive 2002/96/EC – WEEE (Waste Electrical and Electronic Equipment). For questions, contact your local authority responsible for disposal.

Warranty

This product is covered by a 24-month warranty. The warranty does not cover damage during transport, damage caused by improper handling, accidents, failure to follow instructions, modifications by third parties, force majeure (e.g., lightning, earthquakes, fire, volcanic eruptions), or damage after the warranty period has expired.

The product complies with EMC 2014/30/EU and RoHS 2011/65/EU. The EU Declaration of Conformity is available from the manufacturer.